
metkan

Bag Conveyor



Transfers filled bags from the filling line to weighing, inspection or palletizing stations in a controlled flow.

APPLICATIONS

Bagged product lines · Post-filling inspection · Palletizing preparation

Operation and maintenance.

Transfers filled bags from the filling line to weighing, inspection or palletizing stations in a controlled flow.

01

Define the product

Bag dimensions, weight and product behaviour are the starting point for selection.

02

Plan the flow


Assess inlet, outlet and transfer points with the other equipment.

03

Coordinate control

Match the conveyor task to line speed and automation requirements.

MACHINE DETAILS



01 Belt width matched to bag dimensions

02 Drive matched to line speed

03 Length and height suited to the layout

Line integration

Belt width, conveyor length, height, drive and control options are determined by bag properties and line layout. This catalogue does not specify fixed dimensions or a guaranteed capacity.

Selection for your line.

Transfers filled bags from the filling line to weighing, inspection or palletizing stations in a controlled flow.

Selection input	Information assessed together
Bag	Bag type, dimensions, weight and surface properties.
Product	Product behaviour inside the bag and bag shape stability.
Line capacity	Bags per hour, line speed and operating pattern.
Layout	Inlet and outlet heights, available space and transfer points.
Control	Signal coordination with filling, weighing, rejection and palletizing equipment.
Maintenance	Access areas, cleaning and periodic inspection requirements.

Selection notes

Belt width, conveyor length, height, drive and control options are determined by bag properties and line layout. This catalogue does not specify fixed dimensions or a guaranteed capacity.

metkan

From machine to plant. Engineering in every detail.

Metkan develops machinery and plant solutions for construction chemicals, minerals and aggregates. At our manufacturing centre in Elbistan, we consider equipment together with feeding, conveying and production flow.

Four inputs for selection

01 **Material and product**

Material properties; for bagged products, bag type, dimensions and weight.

02 **Process target**

Inlet conditions, required product and the next production stage.

03 **Production target**

Target hourly capacity, operating hours and production pattern.

04 **Installation**

Inlet/outlet levels, connections, drive and maintenance access.

Projects and sales

sales@metkanmakine.com
info@metkanmakine.com
+90 216 759 93 23
+90 532 386 74 46

Manufacturing centre

Çiçek OSB Mahallesi 1. Sokak No:11
Elbistan / Kahramanmaraş, Türkiye

metkanglobal.com

Catalogue data support preliminary selection. Final capacity, power, dimensions and supply scope are defined in the technical quotation. Images represent the product family; configurations may vary.